

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A61F 13/15, 13/20</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/24097</b> <b>(43) International Publication Date:</b> 10 July 1997 (10.07.97)
<b>(21) International Application Number:</b> PCT/US96/20712 <b>(22) International Filing Date:</b> 19 December 1996 (19.12.96)  <b>(30) Priority Data:</b> 95120653.1 28 December 1995 (28.12.95) EP <i>(34) Countries for which the regional or international application was filed:</i> BE et al.  <b>(71) Applicant (for all designated States except US):</b> THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> BEWICK-SONNTAG, Christopher, Philip [GB/IT]; Via Giorgione, 9, I-65125 Pescara (IT). VEGLIO, Paolo [IT/IT]; Via Piomba, 23, I-65100 Pescara (IT).  <b>(74) Agents:</b> REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> ABSORBENT ARTICLES HAVING A SEPARATING MEANS  <b>(57) Abstract</b>  The present invention relates to absorbent articles having a topsheet, an absorbent core and a breathable backsheet, wherein at least one of the layers below and including the core is separated from an adjacent layer in order to inhibit wet-through.		



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

5

## **Absorbent articles having a separating means**

10

### **Field of the Invention**

The present invention relates to absorbent articles in particular sanitary napkins having a breathable backsheet, which exhibit reduced wet  
15 through onto the users garments.

### **Background of the Invention**

The primary consumer needs which underlie development in the  
20 absorbent article field, in particular catamenials is the provision of products providing both a high protection and comfort level.

One highly desirable means for improving the comfort of absorbent articles is the use of so called 'breathable backsheets'. Breathable  
25 backsheets may typically comprise either a microporous film or an apertured formed film having directional fluid transfer as disclosed in for example US 4 591 523. Both types of breathable backsheets are vapour permeable, allowing gaseous exchange with the environment. This thereby allows for the evaporation of a portion of the fluid stored in the core and  
30 increases the circulation of air within the absorbent article. This is particularly beneficial as it reduces the sticky feeling experienced by many wearers during use, particularly over extended periods of time.

However, the main drawback associated with the use of breathable  
35 backsheets in absorbent articles is the increased probability of leakage, commonly referred to as wet through, onto the users garment. Although the breathable backsheets in principle only allow the transfer of materials in the gaseous state, physical mechanisms such as xtrusion, diffusion and capillary action may still occur and result in the transfer of the fluids from

the absorbent core through the backsheet and onto the users garments. In particular, these mechanisms become more dominant if the product is utilised during physical exertion, for heavy discharge loads or over extended periods of time. Thus, whilst the incorporation of breathable  
5 backsheets in absorbent articles is highly desirable from a comfort standpoint, they result in an unacceptable level of failure with regard to protection, especially under stressed conditions.

10 The problem of wet through onto users garments due to the incorporation of such breathable backsheets in absorbent articles has been recognised in the art. However attempts to solve the problem have mainly resided in the use of multiple layer backsheets such as those illustrated in US 4 31 216. Similarly unpublished European patent application no. 94203228 discloses a breathable backsheet for disposable absorbent  
15 articles comprising an outer layer of a gas permeable, hydrophobic, polymeric fibrous fabric and an inner layer comprising an apertured formed film having directional fluid transport. Also unpublished European patent application no. 94203230 discloses breathable absorbent articles comprising a breathable backsheet consisting of at least two breathable  
20 layers which are unattached to one another over the core area.

However, none of the above solutions have proved fully satisfactory in providing a satisfactory solution to the problem of backsheet wet through. Furthermore, the problem of wet through is further accentuated in  
25 the case of so called thin products, which are again desirable from a comfort standpoint. Thus, there exists a dichotomy in the means available to provide increased comfort absorbent products, such that thin breathable products cannot provide the desired level of protection.

30 As a result, there exists a need to provide an absorbent article which offers improved comfort by the employment of a breathable backsheet and having a reduced thickness which maintains the required level of protection.

35 It has now been found that breathable backsheets may be utilised in sanitary napkins having reduced thickness, thereby providing a product having both a high level of protection and comfort by the utilisation of a separating means between any adjacent layers below and including the

core. It is believed that the separation of the layers, particularly the core from the breathable backsheet thereby minimising the contact between these layers hinders the movement of fluid through the backsheet onto the users garments thereby preventing wet through.

Separating means have been previously disclosed in the context of absorbent articles, such as for example EPO 555 341. However, this document does not disclose breathable backsheets or recognise the problems associated with the use of such breathable backsheets.

### Summary of the Invention

The present invention is a disposable absorbent article comprising, a liquid pervious topsheet, an absorbent core and a breathable backsheet. The absorbent core is positioned intermediate the topsheet and the backsheet, and each comprise at least one layer, the core comprising a fluid storage layer and the backsheet comprising an outer layer. Each of the layers has a wearer facing surface and a garment facing surface and each of these wearer facing surfaces forms a common interface with an adjacent garment facing surface of an adjacent layer. The article has a backsheet portion extending from the garment facing surface of the fluid storage layer to the garment facing surface of the outer layer.

The present invention is characterised in that at least one garment facing surface in the backsheet portion is separated from an adjacent wearer facing surface by a separating means such that not more than 50% of the surface of the common interface is in direct contact.

### Detailed Description of the Invention

The present invention relates to absorbent disposable articles such as sanitary napkins, baby diapers, incontinence products and panty liners. Typically such products comprise a liquid pervious topsheet, a backsheet and an absorbent core intermediate said topsheet and said backsheet. The topsheet, core and backsheet each comprise at least one layer, each of these layers having a wearer facing surface and a garment facing surface. Each of the wearer facing surfaces forms a common interface with an adjacent garment facing surface of an adjacent layer, herein after referred

to as common interface. The common interface extends to the same area as those portions of the respective garment and wearer facing surfaces which are coextensive.

5       The absorbent article has a backsheet portion extending from the garment facing surface of the storage layer to the garment facing surface of the outer layer of the backsheet. The backsheet portion is herein after referred to as any layer below and including the core.

10       According to a preferred embodiment of the present invention the absorbent article comprises sideflaps, side wrapping elements or wings.

#### Separating means

15       According to the present invention the absorbent article comprises as an essential feature a separating means. The term separating means as used herein refers to any device which separates the common interface of two adjacent surfaces as defined above. Common interfaces which may be thus separated include the garment facing surface of the fluid storage layer  
20       from the wearer facing surface of the backsheet and any pair of adjacent backsheet layers and any combinations thereof. According to the present invention said garment facing surface and said wearer facing surface are separated from one another such that not more than 50%, preferably not more than 45%, more preferably not more than 40%, most preferably not  
25       more than 30% of the surface of the common interface is in direct contact. It is believed that the separation of at least two adjacent layers below and including the core significantly reduces the occurrence of wet through onto the undergarment which would normally occur with a breathable backsheet.

30       In addition the absorbent article and similarly each layer of said absorbent article has a side portion extending from the periphery of the absorbent article to the centre or central portion of the absorbent article, said central portion being defined as an area which typically receives at  
35       least 75%, of the fluid discharge. The central portion of the absorbent article is thus under the most stress and where the probability of wet through failure is greatest. Therefore in a preferred embodiment direct contact at the common interface surface at this central portion should be

minimised and is preferably such that not more than 50%, preferably not more than 40%, most preferably not more than 30% of said central portion of said surface of said common interface is in direct contact.

5 According to the present invention said separating means may be any means whereby a common interface of two adjacent layers in the backsheet portion of the article are separated from one another and thus include those described in EPO 555 341 which are incorporated herein by reference.

10

The separating means of the present invention has a longitudinal centre line and transverse centre line which may be used to describe the position and orientation of the separating means under the core of the absorbent article. The separating means may be placed in various  
15 locations under the absorbent core. For instance the separating means may be centred relative to the other components of the absorbent article so that the longitudinal and transverse lines of the separating means coincide with the principal longitudinal and transverse centrelines of the absorbent article. Alternatively, the separating means may be positioned so that it is  
20 not centred on the absorbent article such that the longitudinal and transverse centrelines of the separating means and the absorbent article are offset.

The separating means may have any configuration provided that it  
25 separates two adjacent layers as described herein above. Hence, the separating means may be symmetrical or unsymmetrical about its principal longitudinal and transverse centrelines.

The configuration of the separating means may be described in terms  
30 of its longitudinal and transverse dimensions. Typically, the longitudinal dimensions of the separating means are greater than the transverse dimensions. The separating means can extend up to 100% of the length and of the width of any of the surfaces of the layers which it separates. In addition, in order to minimise the effect on the overall thickness of the  
35 absorbent article the separating means should be thin and preferably have a thickness or depth less than 1mm preferably less than 0.5mm.



The separating means may be comprised of one element or a number of elements provided that separation between the layers is achieved. Preferably, the separating means comprises one element. Similarly, the separating means may be comprised of the same piece and type of material or may be comprised of separate pieces or types of material. Preferably the separating means is comprised of one piece of material which is unitary.

According to the present invention the separating means may be made of any material provided that it does not substantially hinder the transfer of gaseous materials between the layers which it separates. Suitable materials for the separating means include polymeric materials such as polyethylene, polypropylene and adhesive materials which can be chosen depending on the configuration of the separating means and the degree of stability required.

In one preferred embodiment of the present invention said separating means comprises a lattice which is centred with the absorbent article and extends to the periphery of the absorbent article. The lattice may have any dimension depending on the configuration of the separating means but preferably has a net-like configuration. Typically the lattice comprises openings having an average diameter of at least 100 micrometers, preferably at least 150 micrometers, most preferably at least 200 micrometers. Materials suitable for use as a lattice separating means include adhesives and polypropylene.

In another preferred embodiment of the present invention said separating means is comprised of a sheet material. The sheet material may be planar, folded or pleated as described for example in EPO 555 341. Particularly suitable material includes an apertured planar polymer material or an apertured formed polymeric film, the apertures having an average diameter of at least 100 micrometers, preferably at least 150 micrometers, most preferably at least 200 micrometers.

### Backsheet

The absorbent articles according to the present invention comprise a breathable backsheet. The backsheet primarily prevents the extrudes

absorbed and contained in the absorbent structure from wetting articles that contact the absorbent product such as underpants, pants, pyjamas and undergarments. In addition however, the breathable backsheet of the present invention permits the transfer of both vapour and air through it and thus allows the circulation of air into and out of the backsheet.

According to the present invention the breathable backsheet comprises at least one gas permeable layer. Suitable gas permeable layers include 2 dimensional, planar micro and macro-porous films, macroscopically expanded films and formed apertured films. According to the present invention the apertures in said layer may be of any configuration, but are preferably spherical or oblong and may also be of varying dimensions. Typically, said layers have apertures having average diameters of from 150 micrometers to 5 micrometers, preferably from 120 micrometers to 10 micrometers, most preferably from 90 micrometers to 15 micrometers. The apertures preferably are evenly distributed across the entire surface of the layer, however layers having only certain regions of the surface having apertures is also envisioned.

Suitable 2 dimensional planar layers of the backsheet may be made of any material known in the art, but are preferably manufactured from commonly available polymeric materials. Suitable materials are for example Gortex (TM) or Sympatex (TM) type materials well known in the art for there application in so-called breathable clothing. Other suitable materials include XMP-1001 of Minnesota Mining and Manufacturing Company, St. Paul, Minnesota, USA. As used herein the term 2 dimensional planar layer refers to layers having a depth of less than 1mm, preferably less than 0.5mm, wherein the apertures all lie within the plane and do not protrude out of the plane of the layer. The apertured materials for use as a backsheet in the present invention may be produced using any of the methods known in the art such as described in EPO 293 482 and the references therein. In addition the dimensions of the apertures produced by this method may be increased by applying a force across the plane of the backsheet layer (i.e. stretching the layer).

Suitable apertured formed films include films which have discrete apertures which extend beyond the horizontal plane of the garment facing surface of the layer towards the core thereby forming protuberances. The

protuberances have an orifice located at its terminating end. Preferably said protuberances are of a funnel shape, similar to those described in US 3, 929,135. The apertures located within the plane and the orifices located at the terminating end of protuberance themselves may be circular or non circular provided the cross sectional dimension or area of the orifice at the termination of the protuberance is smaller than the cross sectional dimension or area of the aperture located within the garment facing surface of the layer. Preferably said apertured preformed films are uni directional such that they have at least substantially, if not complete one directional fluid transport towards the core. Suitable macroscopically expanded films for use herein include films as described in for example in US 637 819 and US 4 591 523.

According to the present invention the backsheet may comprise in addition to said gas permeable layer additional backsheet layers. Said additional layers are located adjacent and below said gas permeable layer towards the garment facing surface of the outer layer. The additional layers may be of any material preferably such that they do not reduce the gas permeability of the backsheet.

The backsheet typically extends across the whole of the absorbent structure and can extend into and form part of or all sideflaps, side wrapping elements or wings.

According to the present invention the absorbent article can be used beneficially in the context of sanitary napkins, panty liners, incontinence articles and diapers. However, sanitary napkins and panty liners are particularly susceptible to the present invention. The disposable article may thus have all those features and parts which are typical for products in the context of their intended use. In addition to the components previously described they typically comprise a topsheet and absorbent core.

#### Absorbent core

According to the present invention, the absorbent core can include the following components: (a) an optional primary fluid distribution layer preferably together with a secondary optional fluid distribution layer; (b) a fluid storage layer; (c) an optional fibrous ("dusting") layer underlying the

storage layer; and (d) other optional components. According to the present invention the absorbent core may have any thickness depending on the end use envisioned. In a preferred embodiment of the present invention wherein the absorbent article is a sanitary napkin or a panty liner, the core may have a thickness of from 15mm to 1mm, preferably from 10mm to 1mm, most preferably from 7mm to 1mm.

a Primary/Secondary Fluid Distribution Layer

One optional component of the absorbent core according to the present invention is a primary fluid distribution layer and a secondary fluid distribution layer. The primary distribution layer typically underlies the topsheet and is in fluid communication therewith. The topsheet transfers the acquired fluid to this primary distribution layer for ultimate distribution to the storage layer. This transfer of fluid through the primary distribution layer occurs not only in the thickness, but also along the length and width directions of the absorbent product. The also optional but preferred secondary distribution layer typically underlies the primary distribution layer and is in fluid communication therewith. The purpose of this secondary distribution layer is to readily acquire fluid from the primary distribution layer and transfer it rapidly to the underlying storage layer. This helps the fluid capacity of the underlying storage layer to be fully utilised. The fluid distribution layers can be comprised of any material typical for such distribution layers.

b Fluid Storage Layer

Positioned in fluid communication with, and typically underlying the primary or secondary distribution layers, is a fluid storage layer. The fluid storage layer can comprise any usual absorbent material or combinations thereof. It preferably comprises absorbent gelling materials usually referred to as "hydrogel", "superabsorbent", hydrocolloid" materials in combination with suitable carriers.

The absorbent gelling materials are capable of absorbing large quantities of aqueous body fluids, and are further capable of retaining such absorbed fluids under moderate pressures. The absorbent gelling materials can be dispersed homogeneously or non-homogeneously in a suitable

carrier. The suitable carriers, provided they are absorbent as such, can also be used alone.

Suitable absorbent gelling materials for use herein will most often comprise a substantially water-insoluble, slightly cross-linked, partially neutralised, polymeric gelling material. This material forms a hydrogel upon contact with water. Such polymer materials can be prepared from polymerizable, unsaturated, acid-containing monomers which are well known in the art.

Suitable carriers include materials which are conventionally utilised in absorbent structures such as natural, modified or synthetic fibers, particularly modified or non-modified cellulose fibers, in the form of fluff and/or tissues. Suitable carriers can be used together with the absorbent gelling material, however, they can also be used alone or in combinations. Most preferred are tissue or tissue laminates in the context of sanitary napkins and panty liners.

An embodiment of the absorbent structure made according to the present invention comprises a double layer tissue laminate formed by folding the tissue onto itself. These layers can be joined to each other for example by adhesive or by mechanical interlocking or by hydrogen bridge bands. Absorbent gelling material or other optional material can be comprised between the layers.

Modified cellulose fibers such as the stiffened cellulose fibers can also be used. Synthetic fibers can also be used and include those made of cellulose acetate, polyvinyl fluoride, polyvinylidene chloride, acrylics (such as Orion), polyvinyl acetate, non-soluble polyvinyl alcohol, polyethylene, polypropylene, polyamides (such as nylon), polyesters, bicomponent fibers, tricomponent fibers, mixtures thereof and the like. Preferably, the fiber surfaces are hydrophilic or are treated to be hydrophilic. The storage layer can also include filler materials, such as Perlite, diatomaceous earth, Vermiculite, etc., to improve liquid retention.

If the absorbent gelling material is dispersed non-homogeneously in a carrier, the storage layer can nevertheless be locally homogenous, i.e. have a distribution gradient in one or several directions within the

dimensions of the storage layer. Non-homogeneous distribution can also refer to laminates of carriers enclosing absorbent gelling materials partially or fully.

5

c Optional Fibrous ("Dusting") Layer

10 An optional component for inclusion in the absorbent core according to the present invention is a fibrous layer adjacent to, and typically underlying the storage layer. This underlying fibrous layer is typically referred to as a "dusting" layer since it provides a substrate on which to deposit absorbent gelling material in the storage layer during manufacture of the absorbent core. Indeed, in those instances where the absorbent  
15 gelling material is in the form of macro structures such as fibers, sheets or strips, this fibrous "dusting" layer need not be included. However, this "dusting" layer provides some additional fluid-handling capabilities such as rapid wicking of fluid along the length of the pad.

20

d Other Optional Components of the absorbent structure

The absorbent core according to the present invention can include other optional components normally present in absorbent webs. For example, a reinforcing scrim can be positioned within the respective layers, or between the respective layers, of the absorbent core. Such reinforcing  
25 scrims should be of such configuration as to not form interfacial barriers to fluid transfer. Given the structural integrity that usually occurs as a result of thermal bonding, reinforcing scrims are usually not required for thermally bonded absorbent structures.

30

Another component which can be included in the absorbent core according to the invention and preferably is provided close to or as part off the primary or secondary fluid distribution layer are odor control agents. Active carbon coated with or in addition to other odor control agents, in  
35 particular suitable zeolite or clay materials, are optionally incorporated in the absorbent structure. These components can be incorporated in any desired form but often are included as discrete particles.

### The topsheet

The topsheet may comprise a single layer or a multiplicity of layers. In a preferred embodiment the topsheet comprises a first layer which provides the user facing surface of the topsheet and a second layer between the first layer and the absorbent structure/core.

The topsheet as a whole and hence each layer individually needs to be compliant, soft feeling, and non-irritating to the wearer's skin. It also can have elastic characteristics allowing it to be stretched in one or two directions. According to the present invention the topsheet may be formed from any of the materials available for this purpose and known in the art, such as non woven fabrics, films or combinations of both. In a preferred embodiment of the present invention at least one of the layers of the topsheet comprises a hydrophobic, liquid permeable apertured polymeric film. Preferably, the upper layer is provided by a film material having apertures which are provided to facilitate liquid transport from the wearer facing surface towards the absorbent structure, as detailed for example in US 3 929 135, US 4 151 240, US 4 319 868, US 4 324 426, US 4 343 314 and US 4 591 523.

The topsheet typically extends across the whole of the absorbent structure and can extend into and form part of or all of the preferred sideflaps, side wrapping elements or wings.

According to the present invention the absorbent article is constructed by joining the various elements such as topsheet, backsheet and absorbent core by any means well known in the art. For example the backsheet and/or topsheet may be joined to the absorbent core or to each other by a uniform continuous layer of adhesive, a patterned layer of adhesive, or any array of separate lines, spirals or spots of adhesive. Alternatively, the elements may be joined by heat bonds, pressure bonds, ultra sonic bonds, dynamic mechanical bonds or any other suitable joining means known in the art and any combination thereof.

### Examples

#### Undergarment Wt-through Evaluation Test

An undergarment wet-through test was carried out on sanitary napkins according to the present invention as detailed below to evaluate the resistance of the backsheet to transmission of bodily discharges.

Method:

This is a test that is performed under realistic in-use conditions. A group of at least 20, for example women menstruating, are given at least 5 sanitary napkins and an equal number of cotton panties. They are instructed to wear the sanitary napkin with the supplied panties as they would normally wear such articles. Following usage the panty is removed with the used napkin still attached and transported to the laboratory for visual assessment of the used napkin and the panty.

The returned napkins are inspected for through backsheet wet-through. In the case of an sanitary napkin worn during menstruation this consists of quantifying the number of panties that feature a reddish blemish greater than  $0.25 \text{ mm}^2$ . For each napkin that has wet-through the breathable backsheet, the quantity of menses, the location of wet-through and magnitude are recorded.

Examples:

Each test sample was prepared under identical conditions in all regards except for the specific aspect detailed in the example description below. All test samples were machine made "Always Ultra Normal" sanitary napkins {manufactured by Procter & Gamble, Pescara Technical Centre SpA, Italy with the modification detailed} according to normal manufacturing procedures to ensure the quality and consistency of the products.

Example 1: (Reference)



In this example the plastic, impervious backsheet typically found on a sanitary napkin is replaced by a microporous film {supplied by Exxon Chemical Company under the manufacturing code Exxaire XBF-100W} and positioned directly in contact with the absorbent core.

5

**Example 2:**

In this example in addition to replacing the backsheet with a microporous film {supplied by Exxon Chemical Company under the manufacturing code Exxaire XBF-100W} as described in example 1 an additional layer has been inserted between the absorbent core and the microporous film. This layer is a one-direction (towards the core) fluid transporting apertured film made of low Density PE {supplied by Tredegar Corporation, USA under the manufacturing code X-1522}.

15

**Table 1:** Laboratory Assessment of wet-through on returned sanitary napkins.

Example	Ave. Load at Failure (grams)	% Pads with Wet-Through
Example 1	6.6	22 %
Example 2	18.5	< 2 %

20

## WHAT IS CLAIMED IS:

1. A disposable absorbent article comprising, a liquid pervious topsheet,  
5 an absorbent core and a breathable backsheet, said absorbent core  
being positioned intermediate said topsheet and said backsheet, said  
topsheet, core and backsheet each comprising at least one layer, said  
core comprising a fluid storage layer, said backsheet comprising an  
outer layer,  
10 each of said layers having a wearer facing surface and a garment  
facing surface and each of said wearer facing surfaces forming a  
common interface with an adjacent garment facing surface of an  
adjacent layer,  
15 said article has a backsheet portion extending from said garment  
facing surface of said fluid storage layer to said garment facing  
surface of said outer layer and  
20 wherein at least one garment facing surface in said backsheet portion  
is separated from an adjacent wearer facing surface by a separating  
means such that not more than 50% of the surface of said common  
interface is in direct contact.
- 25 2. A disposable absorbent article according to claim 1, wherein not more  
than 45% of the surface of said common interface is in direct contact.
3. A disposable absorbent article according to any one of the preceding  
claims, wherein said breathable backsheet comprises at least one  
30 layer which is a 2-dimensional polymeric apertured film.
4. A disposable absorbent article according to claim 3, wherein said  
apertures have average diameters of from 150 micrometers to 5  
micrometers.  
35
5. A disposable absorbent article according to any one of the preceding  
claims wherein said separating means is gas permeabl .

6. A disposable absorbent article according to any one of the preceding claims, wherein said separating means comprises apertures having an average diameter of at least 100 micrometers.
- 5 7. A disposable absorbent article according to any one of the preceding claims wherein said separating means is a 2-dimensional apertured polymeric film or an apertured formed polymeric film.
- 10 8. A disposable article according to any one of the preceding claims, wherein said common interface comprises a central portion and a side portion and wherein not more than 50% of said central portion of the surface of said common interface forms a direct contact.
- 15 9. A disposable absorbent article according to any one of the preceding claims wherein said article is a sanitary napkin or a panty liner.

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US96/20712

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61F 13/15, 20

US CL : 604/378, 385.1

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 604/378, 385.1

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,346,487 A (LOVESTEDT) 13 September 1994, cols. 3 and 4.	1-4
Y,P	US 5,527,303 A (MILBY, Jr. et al.) 18 June 1996, col. 5, lines 7-9.	1-4

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G*	document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means		
*P* document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

24 FEBRUARY 1997

Date of mailing of the international search report

12 MAR 1997

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3590

Authorized Officer

P. ZUTTARELLI

Telephone No. (703) 308-3055

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US96/20712

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
  
2. ☐ Claims Nos.:  
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
  
3. ☒ Claims Nos.: 5-9  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
  
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.  
☐ No protest accompanied the payment of additional search fees.

